US009636521B2

(12) **United States Patent**
Isserow et al.

(10) **Patent No.: US 9,636,521 B2**
(45) **Date of Patent: May 2, 2017**

(54) **HEAT AND LIGHT TREATMENT DEVICE USING NANOTECHNOLOGY**

(71) Applicants: **Jonathan Isserow**, Basking Ridge, NJ (US); **Laura Isserow**, Basking Ridge, NJ (US)

(72) Inventors: **Jonathan Isserow**, Basking Ridge, NJ (US); **Laura Isserow**, Basking Ridge, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 164 days.

(21) Appl. No.: **13/940,307**

(22) Filed: **Jul. 12, 2013**

(65) **Prior Publication Data**

US 2015/0013214 A1 Jan. 15, 2015

(51) **Int. Cl.**
A61N 5/06 (2006.01)
A61F 7/00 (2006.01)

(52) **U.S. Cl.**
CPC ***A61N 5/062*** (2013.01); ***A61F 7/007*** (2013.01); ***A61N 5/0616*** (2013.01); ***A61N 5/0625*** (2013.01); *A61F 2007/0078* (2013.01); *A61N 2005/0647* (2013.01)

(58) **Field of Classification Search**
CPC A61F 2007/0226
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,658,583 A 8/1997 Zhang et al.
6,205,016 B1 3/2001 Niu
6,414,836 B1 7/2002 Tennent et al.
6,586,133 B1 7/2003 Teeters et al.
6,665,169 B2 12/2003 Tennent et al.
7,116,546 B2 10/2006 Chow et al.
(Continued)

FOREIGN PATENT DOCUMENTS

GB 2515010 A * 12/2014
WO 2010123528 10/2010
(Continued)

OTHER PUBLICATIONS

Using Freezing Conditions to Kill Bed Bugs, webpage from https://web.archive.org/web/20121115090510/http://www.bedbugs.umn.edu/bed-bug-control-in-residences/using-freezing-temperatures-for-bedbug-control, University of Minnesota (Nov. 15, 2012).*
(Continued)

Primary Examiner — Joseph Stoklosa
Assistant Examiner — Nicole L Pobre
(74) *Attorney, Agent, or Firm* — Gearhart Law LLC

(57) **ABSTRACT**

The current invention discloses a treatment device having a heat source, a power source, a heat applicator and a lighting mechanism. The power source includes at least one nanotech battery, ensuring superior properties such as prolonged electricity production and prompt recharging. The heat applicator includes a heat conductive layer made from nanofibers, providing highly efficient heat distribution to the targeted regions. The lighting mechanism employs light emitting nano fibers to treat targeted regions. The power source provides energy to the heat and light source, which generates heat and light so that the applicator may distribute to an injury site or wound bed of a user. The current device may also be used for cooling, instead of heating applications. In addition to the medical utilizations, the current device may also play a central role in other apparatus that require thermal control capabilities.

17 Claims, 2 Drawing Sheets